

Item:
Quantity:
Project:

Delux Series

Models: ☐ SPR-180 ☐ SPR-360 ☐ SPR-540 ☐ SSPR-110 ☐ SSPR-220	
-------------------------------------------------------------	--



Elevation (if above 2000 ft.): __

Standard Features

- Fully welded chassis
- Compact, heavy gauge chassis for long life
- Stainless steel sides and front valve cover
- Stainless steel tubing for pilots
- Stainless steel drip pan
- Cast iron top grate

Stock Pot Range: SPR

- Heavy, cast iron three-ring outer burner, rated at a total of 50,000 BTU/hr, outer ring at 35,000, inner ring 15,000 BTU/hr for slow simmering of product
- Two Manual controls to operate the inner and outer rings independently for maximum flexibility of usage
- Available in 1,2 and 3 side by side units

Stock Pot Range: SSPR

- Heavy, cast iron three-ring outer burner, rated at a total of 100,000 BTU/hr, outer ring at 50,000, inner ring 50,000 BTU/hr for quick boiling of product
- Two Manual controls to operate the inner and outer rings independently for maximum flexibility of usage
- Available in 1 or 2 side by side units

Options and Accessories

- ☐ 5" swivel casters (set of four 2 locking)
- □ 5" swivel casters (set of six 3 locking) for double and triple stock pots









Model Number	Width	Depth	Height	Burners	Total BTU	Ship Weight
SPR-180	18"	21"	25"	1	50,000	110 lbs.
SPR-360	36"	21"	25"	1	100,000	255 lbs.
SPR-540	54"	21"	25"	1	150,000	320 lbs.
SSPR-110	18"	21"	25"	1	100,000	125 lbs.
SSPR-220	36"	21"	25"	1	200,000	255 lbs.

Notes:

Gas Connection:

3/4" NPT on the right hand rear of the appliance.

The pressure regulator (supplied) is to be connected by the installer.

Specify type of gas and altitude, if over 2,000 feet, when ordering.

Gas Pressure:

5" W.C.	Natural Gas
10" W.C.	Propane

Clearances:

	Combustible	Non-Combustible
Rear	17"	4"
Sides	15"	0"

Due to continuing product development to ensure best possible performance, these specifications are subject to change without prior notification.